K-16

Japanese Kokai Patent Application No. Hei 11[1999]-57278 [Claims only, as requested]

Code: 5000-72374

## JAPANESE PATENT OFFICE PATENT JOURNAL KOKAI PATENT APPLICATION NO. HEI 11[1999]-57278

Int. Cl.6:

D 06 F 35/00

A 47 G 25/14

Application No.:

Hei 9[1997]-225426

Application Date:

August 21, 1997

**Publication Date:** 

March 2, 1999

No. of Claims:

9 (Total of 8 pages; OL)

**Examination Request:** 

Requested

## HANGER FOR LAUNDRY NET

Inventors:

Yoshimi Saigusa

c/o Kao K.K. Research Laboratory 2-1-3 Bunka, Sumida-ku, Tokyo

Makoto Kato

c/o Kao K.K. Research Laboratory 2-1-3 Bunka, Sumida-ku, Tokyo

Fumihiko Sedai

c/o Kao K.K. Research Laboratory 2-1-3 Bunka, Sumida-ku, Tokyo

Nobuko Hasegawa

c/o Kao K.K. Research Laboratory 2-1-3 Bunka, Sumida-ku, Tokyo

Applicant:

000000918

Kao K.K.

1-14-10 Nihonbashi Kayaba-cho,

Chuo-ku, Tokyo

\* \* \*

## Claims

- 1. A hanger for a laundry net, characterized by the fact that it is a hanger for a laundry net which is used by being placed within a laundry net during the washing of clothes, the hanger comprises a shaft part and two end part members which interfit externally to the two ends of the shaft part and the shaft part ends take on a state of having been inserted, the inserting depth of the shaft part into the end part members is variable continuously, and the shaft part and the end part members are stopped with a sliding force.
- 2. A hanger for laundry net noted in Claim 1, in which the sliding force during the drying of the shaft part and the end part members when changing the inserting depth of the shaft part to the end part members is 9-40 N.
- 3. A hanger for laundry net noted in Claim 1 or 2, in which a cylindrical shape slider is interfit to the end on the shaft part side of the end part member.
- 4. A hanger for laundry net noted in Claim 3, in which the end part members are composed of a foaming resin and the cylindrical slider and the shaft part are composed of a nonfoaming resin.
- 5. A hanger for laundry net noted in Claim 4, in which the end part members are composed of a foaming polyethylene resin and the shaft part is composed of a polypropylene resin.
- 6. A hanger for laundry net noted in one of Claims 1-5, in which the buoyancy of the hanger is 30-500 g.
- 7. A hanger for laundry net noted in one of Claims 3-6, in which a stopper part with a larger diameter than the minor diameter of the cylindrical shape slider is provided to both ends of the shaft part.
- 8. A hanger for laundry net noted in Claim 7, in which a slit is formed in the stopper part in the longitudinal direction from the end thereof.
- 9. A hanger for laundry net noted in one of Claims 1-8, which has a clamp for attaching the hanger to the laundry net to be freely attachable and detachable.

\* \* \*

This Page Blank (uspto)